

Our Solutions, Your Value

Model ID	NPM-W2						
Front head	Rear head	Lightweight 16-nozzle head	12-nozzle head	8-nozzle head	3-nozzle head	Dispensing head	No head
Lightweight 16-nozzle head		NM-EJM7D				NM-EJM7D-MD	NM-EJM7D
12-nozzle head							
8-nozzle head							
3-nozzle head							
Dispensing head		NM-EJM7D-MD					NM-EJM7D-D
Inspection head		NM-EJM7D-MA					NM-EJM7D-A
No head		NM-EJM7D				NM-EJM7D-D	
PCB dimensions	Single-lane *1	Batch mounting	L 50 mm × W 50 mm ~ L 750 mm × W 550 mm		2-position mounting	L 50 mm × W 50 mm ~ L 350 mm × W 550 mm	
	Dual-lane *1	Single transfer	L 50 mm × W 50 mm ~ L 750 mm × W 510 mm		Dual transfer	L 50 mm × W 50 mm ~ L 750 mm × W 260 mm	
Electric source	3-phase AC 200, 220, 380, 400, 420, 480 V 2.8 kVA						
Pneumatic source *2	0.5 MPa, 200 L / min (A.N.R.)						
Dimensions *2	W 1 280 mm *3 × D 2 332 mm *4 × H 1 444 mm *5						
Mass	2 470 kg (Only for main body. This differs depending on the option configuration.)						
Placement head	Lightweight 16-nozzle head (With Dual Heads)		12-nozzle head (With Dual Heads)		8-nozzle head (With Dual Heads)		3-nozzle head (With Dual Heads)
	High production mode[ON]		High production mode[OFF]		High production mode[ON]		High production mode[OFF]
Placement speed	Max. speed	77 000cph (0.047 s/ chip)	70 000cph (0.051 s/ chip)	64 500cph (0.056 s/ chip)	62 500cph (0.058 s/ chip)	40 000cph (0.090 s/ chip)	16 000cph (0.225 s/ chip) 12 500cph (0.288 s/ QFP)
	IPC9850 (1608)	59 200cph *6	56 000cph *6	49 500cph *6	48 000cph *6		
Placement accuracy (Cpk ≥ 1)		±40 μm / chip	±30 μm / chip (±25 μm / chip) *7	±40 μm / chip	±30 μm / chip	±30 μm / chip ±30 μm / QFP □12 mm ~ □32 mm ±50 μm / QFP □12 mm Under	±30 μm / QFP
	Component dimensions (mm)	0402*8 chip ~ L 6 × W 6 × T 3 Tape : 8 / 12 / 16 / 24 / 32 / 44 / 56 mm		03015*8 / 0402*8 chip ~ L 6 × W 6 × T 3 Tape : 8 to 56 mm		0402*8 chip ~ L 32 × W 32 × T 12 Tape : 8 to 56 mm	
Component supply	Taping	Max. 120 8 mm tape : Max. 68 (8 mm thin type single feeder, double tape feeder, small reel)				Front/rear feeder cart specifications : Max. 120 (Tape width and feeder are subject to the conditions on the left) Single tray specifications : Max. 86 (Tape width and feeder are subject to the conditions on the left) Twin tray specifications : Max. 60 (Tape width and feeder are subject to the conditions on the left)	
	Stick					Front/rear feeder cart specifications : Max. 14 Single tray specifications : Max. 10 Twin tray specifications : Max. 7	
	Tray					Single tray specifications : Max. 20 Twin tray specifications : Max. 40	
Dispensing head	Dot dispensing			Draw dispensing			
Dispensing speed	0.16 s/dot (Condition : XY=10 mm, Z=less than 4 mm movement, No θ rotation)			4.25 s/component (Condition: 30 mm x 30 mm corner dispensing)*10			
Adhesive position accuracy (Cpk ≥ 1)	± 75 μm/dot			± 100 μm/component			
Applicable components	1608 chip to SOP, PLCC, QFP, Connector, BGA, CSP			BGA, CSP			
Inspection head	2D inspection head(A)			2D inspection head(B)			
Resolution	18 μm			9 μm			
View size	44.4 mm × 37.2 mm			21.1 mm × 17.6 mm			
Inspection processing time	Solder Inspection *11	0.35s/ View size			0.35s/ View size		
	Component Inspection *11	0.5s/ View size			0.5s/ View size		
Inspection object	Solder Inspection *11	Chip component : 100 μm × 150 μm or more (0603 / 0201* or more) Package component : φ 150 μm or more			Chip component : 80 μm × 120 μm or more (0402 / 01005* or more) Package component : φ 120 μm or more		
	Component Inspection *11	Square chip (0603 / 0201* or more), SOP, QFP (a pitch of 0.4mm or more), CSP, BGA, Aluminum electrolysis capacitor, Volume, Trimmer, Coil, Connector *12			Square chip (0603 / 0201* or more), SOP, QFP (a pitch of 0.4mm or more), CSP, BGA, Aluminum electrolysis capacitor, Volume, Trimmer, Coil, Connector *12		
Inspection items	Solder Inspection *11	Oozing, blur, misalignment, abnormal shape, bridging					
	Component Inspection *11	Missing, shift, flipping, polarity, foreign object inspection *13					
Inspection position accuracy (Cpk ≥ 1) *14	± 20 μm			± 10 μm			
No. of inspection	Solder Inspection *11	Max. 30 000 pcs./machine (No. of components : Max. 10 000 pcs./machine)					
	Component Inspection *11	Max. 10 000 pcs./machine					

* Placement tact time, inspection time and accuracy values may differ slightly depending on conditions. *4 : Dimension D including tray feeder : 2 570 mm
Dimension D including feeder cart : 2 465 mm
*11 : One head cannot handle solder inspection and component inspection at the same time.
*12 : Please refer to the specification booklet for details.
*13 : Foreign object is available to chip components. (Excluding 03015 mm chip)
*14 : This is the solder inspection position accuracy measured by our reference using our glass PCB for plane calibration. It may be affected by sudden change of ambient temperature.

* Please refer to the specification booklet for details.
*5 : Excluding monitor and signal tower
*6 : It is the reference value of the tact time by the IPC9850 conformity. (The independent mode)
*7 : ±25 μm placement support option. (Under conditions specified by PFSC)
*8 : The 03015/0402 chip requires a specific nozzle/feeder.
*9 : Support for 03015 mm chip placement is optional. (Under conditions specified by PSFC : Placement accuracy ±30 μm / chip)

*1 : Please consult us separately should you connect it to NPM-D3/D2/D. It cannot be connected to NPM-TT and NPM.
*2 : Only for main body
*3 : 1 880 mm in width if extension conveyors (300 mm) are placed on both sides.

⚠ Safety Cautions

- Please read the User's Manual carefully to familiarize yourself with safe and effective usage procedures.
- To ensure safety when using this equipment all work should be performed according to that as stated in the supplied Operating Instructions. Read your operating instruction manual thoroughly.



Panasonic Group products are built with the environment in mind.
<http://panasonic.net/eco/>



Panasonic Group builds Environmental Management System in the factories of the world and acquires the International Environmental Standard ISO 14001:2004.

Inquiries...

Panasonic Factory Solutions Co., Ltd.
Corporate SMT Division

1375 Kamisukiawara, Showa-cho, Nakakoma-gun, Yamanashi 409-3895, Japan
TEL +81-55-275-9152
FAX +81-55-275-6269

All data as of January 1, 2015

Ver. January 1, 2015

©Panasonic Factory Solutions Co., Ltd. 2015

● Changes in specifications and appearance may be made without notice for product improvement. ● Recycled paper is used this Catalog.
● Homepage <http://www.panasonic.com/jp/company/pfsc/en.html>

2015
Electronics Assembly System

catalog

PRODUCTION MODULAR



NPM
NEXT PRODUCTION MODULAR

Manufacturing Process Innovation



Model Name **NPM-W2**

Model No. NM-EJM7D

Model No. NM-EJM7D-MD

Model No. NM-EJM7D-D

Model No. NM-EJM7D-MA

Model No. NM-EJM7D-A

*Photograph is NM-EJM7D




*It may not conform to Machinery Directive and EMC Directive in case of optional configuration and custom-made specification.

1 Higher productivity and quality with printing, placement and inspection process integration
Depending on the PCB you produce, you can select High-speed mode or High-accuracy mode.



2 For larger boards and larger components
PCBs up to a size of 750 × 550 mm with component range up to L150 × W25 × T30 mm

3 Higher area productivity through dual lane placement
Depending on the PCB you produce, you can select an optimal placement mode - "Independent" "Alternate" or "Hybrid"



Features Simultaneous realization of high area productivity and high-accuracy placement


- ◆ **High production mode : 10 % increase in productivity / equal placement accuracy** (as compared to NPM-W)
(High production mode: ON) Max. speed: 77 000 cph / Placement accuracy: ±40 μm (Cpk ≥ 1)
- ◆ **High accuracy mode : 25% increase in placement accuracy / equal productivity** (as compared to NPM-W)
(High production mode : OFF) Max. speed: 70 000 cph / Placement accuracy: ±30 μm



Multi-functionality


Large Board

Single-lane specifications (Selection spec.)



Large Board up to 750 × 550 mm can be handled


Dual-lane specifications (Selection spec.)



Large boards (750 × 260 mm) can be handled collectively. Boards (up to a size of 750 × 510 mm) can be handled collectively during single transfer.


Large Components

Compatible to component sizes up to 150 × 25 mm



LED Placement

Brightness Binning



Avoid mixing of brightness and minimizes component and block disposal. Monitors remaining component count to avoid component exhaust during operation.

*Please ask us for nozzles that support LED components of various shapes

Other functions


- Global bad mark recognition function
Reduces in travel/recognition time to recognize bad marks
- PCB standby between machines (with the extension conveyor attached)
Minimizes the PCB (750 mm) change time

High productivity

Alternate, Independent & Hybrid Placement


Selectable "Alternate" and "Independent" dual placement method allows you to make good use of each advantage.

- Alternate: Front and rear heads execute placement on PCBs in front and rear lanes alternately.
- Independent: Front head executes placement on PCB in front lane and rear head execute placement on rear lane.



Independent changeover

In the independent mode, you can conduct a changeover on one lane while production continues on the other lane. You can exchange the feeder cart during the production also with Independent changeover unit (option). It supports automatic support pin replacement (option) and an automatic changeover (option) so that it provides the best changeover for your production type.



PCB exchange time reduction

Two PCBs can be clamped on one stage (PCB length: 350 mm or less). And Higher productivity can be realized by reducing PCB exchange time.

Automatic replacement of support pins (option)

Automate position change of support pins to enable non-stop changeover and help save man-power and operation errors.

Quality improvement

Placement height control function

Based on PCB warpage condition data and thickness data of each of the components to be placed, the control of placement height is optimized to improve mounting quality.

Operating rate improvement

Feeder location free

Within same table, feeders can be set anywhere. Alternate allocation as well as setting of new feeders for next production can be done while the machine is in operation.

Feeders will require off-line data input by support station (option).

Solder Inspection (SPI) · Component Inspection (AOI) Inspection head


Solder Inspection

Solder appearance inspection




Mounted component Inspection

Appearance inspection of mounted components



Pre-mounting foreign object*1 inspection


Pre-mounting foreign object inspection of BGAs
Foreign object inspection right before sealed case placement



*1: Foreign object is available to chip components.


SPI and AOI automatic switching

Solder and component inspection is switched automatically according to production data.




Unification of inspection and placement data

Centrally managed component library or coordinate data does not require two data maintenance of each process.



Automatic link to quality information

Automatically linked quality information of each process assists your defect cause analysis.




Adhesive Dispensing Dispensing head


Screw-type discharge mechanism

Panasonic's NPM has the conventional HDF discharge mechanism, which ensures the high-quality dispensing.

- ① Misalignment prevention of the large-sized component at board transferring
- ② Drop prevention of the back side component at reflowing
- ③ Adhesive reinforcement of BGA and CSP*




Supports various dot/drawing dispensing patterns




High accuracy sensor (option) measures local PCB height to calibrate dispensing height, which allows for non-contact dispensing on PCB.

Self-Alignment Adhesive

Our ADE 400D series is a high-temperature curing SMD adhesive with good component self-alignment effect. This adhesive is also suitable for use in SMT lines to fix bigger components.



After the solder melts, self-alignment and component sinking occurs.




High-quality mounting

APC system*

Feedback to the printing machine


Based on the analyzed measurement data from solder inspections, it corrects printing positions. (X, Y, θ)



*3D inspection equipment of another company can be also connected. Please inquire with your sales representative for more details.

Feedforward to mounting heads

Solder position measurement and feedforward
Chip components (0402C/R ~)
Package component (QFP, BGA, CSP)




Feedforward to AOI

Position inspection on APC offset position

Component Verification option

Prevents setup errors during changeover Provides an increase of production efficiency through easy operation



- Component setup error prevention
Prevents setup errors through verifying the NPM-W2 downloaded production data and component barcode data
- Array data activesync function
There's no need to select array data; data is verified with the NPM-W2
- Interlock function
Equipment stops when it has an incorrect and/or incomplete verification
- Navigation function
Clearly provide a verification task with data display and Intelligent feeder performance in sync
- Scanner selection
Users can choose either a wired or wireless scanner (PDA)


*Please prepare a wireless scanner and related accessories by yourself

High productivity

Automatic changeover option

Supporting changeover (production data and rail width adjustment) can minimize time loss

●PCB ID read-in type
PCB ID read-in function is selectable from among 3 types of external scanner, head camera or planning form



Off-line setup support station

With the support stations, offline feeder cart setup is possible anywhere even outside of the manufacturing floor.

●Two types of Support Stations are available.

①Power Supply Station:
Batch Exchange Cart Setup – Provides power to all feeders in cart. Feeder Setup – provides power to individual feeders.



②Component Verification Station:
Additional to the power supply station, Component Verification feature is added to this model. The station will navigate you to the location where feeders need exchange.



Feeder Setup Navigator

It is a support tool to navigate efficient setup procedure. The tool factors in the amount of time it takes to perform and complete setup operations when estimating the time required for production and providing the operator with setup instructions. This will visualize and streamline setup operations during setup for a production line.

1 Decision making support for production sequence



Estimate production time

2 3 Guidance [set] [out] [move]

No.	作業	割合	部品名	現状	次
1	外し	—	1005Parts-A	1-10L	Reuse
2	外し	—	1005Parts-A	2-12L	Reuse
3	外し	—	1005Parts-A	2-12R	Reuse
4	付け	—	1005Parts-B	新規	1-10L
5	付け	—	1005Parts-C	新規	1-9L
6	付け	—	1005Parts-C	新規	1-9R
7	付け	—	SingleParts-C	新規	1-24S
8	付け	—	1005Parts-B	新規	2-12L
9	付け	—	1005Parts-B	新規	2-12R

3 Change-over process




Follow the instructions
Efficient change-over

Data Creation System

NPM-DGS (Model No.NM-EJS9A)

The software package helps to achieve high productivity through integral management of creation, editing and simulation of production data and library.



*1: A computer must be purchased separately.

*2: NPM-DGS has two management functions of floor and line level.

*3: LNB (Line Network Box) used to connect the machine to NPM-DGS will be installed in FA PC

Multi-CAD import



Almost all CAD data can be retrieved by macro definition registration. Properties, such as polarity, also can be confirmed on screen in advance.

Simulation



Tact simulation can be confirmed on screen in advance so that line total operation ratio can increase.

PPD/LWS Editor




With quickly and easily compiling placement and inspection head data on the PC display during operation, time loss can be minimized

Component library




A component library of all placement machines including the CM series on floor can be registered to unify data management.

Mix Job Setter (MJS)



Production data optimization allows the NPM-D to commonly arrange feeders. Feeder replacement time reduction for changeover can improve productivity

Off-line component data creation option



With creating off-line component data using a store-bought scanner, productivity and quality can be improved.

Offline Camera Unit (option)

Minimizes time on machine for parts library programming and assists equipment availability and quality.

Parts library data is generated using the line camera for NPM-W2. Conditions not possible on a scanner such as Illumination conditions, and recognition speeds, can be checked offline assuring quality enhancements and equipment availability.



Recognition test/Evaluation screen



Offline Camera Unit

Quality improvement

Quality information viewer

This is software designed to support a grasp of changing points and analysis of defect factors through the display of quality-related information (e.g., feeder positions used, recognition offset values and parts data) per PCB or placement point. In case of our inspection head introduced, the defect locations can be displayed in association with quality-related information



*PC is required for every line. It cannot be shared with the NPM-DGS.



Quality information viewer window

Example of use of quality information viewer

Identifies a feeder used for mounting of defect circuit boards. And if, for example, you have many misalignments after splicing, the defect factors can be assumed to be due to:
1) splicing errors (pitch deviation is revealed by recognition offset values)
2) changes in component shape (wrong reel lots or vendors)
So you can take quick action to the misalignment correction.

Open interface

Able to standardize the interfacing with your systems currently used. Provides data communication with our standard interfaces.



Host communication option

- Events
Outputs a real-time event of equipment
 - Other company's component verification
Communicates with your component verification systems
 - Component management data
 - Component remaining quantity data: Outputs component remaining quantity data
 - Trace data: Outputs data linked with component information (*1) and PCB information (*2)
- (*1) Requires input of component information with a component verification option or an other company's component verification system I/F
(*2) Requires input of PCB information with automatic changeover option